

SANI-V EXPLOSION VENTS

DESCRIPTION

Damage to industrial equipment subjected to explosions can be controlled through the use of explosion venting. Explosion venting as a concept introduces a “weak element” in the pressure envelope of the equipment, relieving the internal combustion pressure in case of an explosion.

Fike’s high performance Sani-V™ explosion vents for Clean In Place/ Steam In Place applications were designed:

- With lightweight construction for simplified handling and minimal risk related to damage during installation
- To meet all applicable requirements of NFPA 68, and European Standard for Explosion Venting Devices (EN14797)
- To satisfy the needs for clean production environments



Applicable industries for Fike’s explosion vents include pharmaceutical, biotech, food and beverage, cosmetics, and many others.

FEATURES AND BENEFITS

- No crevices or openings where bacteriological hazards may exist.
- Complies with requirements of general food, beverage, and drug administrations.
- Unique seal offers long-term pressure seal under harsh operating conditions and acts as a bacteriological barrier.
- Provides instantaneous full opening of membrane, eliminating undetected small openings and unwanted risk of contamination.
- No external mounting frame (for most popular burst pressures)
- Vent pressure sealing area protected against mechanical damage
- Excellent service life (positive/vacuum pressures up to 80% of the minimum burst pressure)
- Provides 100% venting efficiency.
- High mechanical integrity
- Certified burst pressure
- Maintenance-free
- Highest operating ratio
- 50% burst pressure vacuum rating
- Fail safe design
- Non-fragmenting
- Compliant with European ATEX-Directive 94/9/EC and NFPA 68 Guidelines

Form No. X.1.11.01-2

SPECIFICATIONS

Materials of Construction (food grade quality):

- Membrane: stainless steel
- Seal: silicone
- Process Gasket: EPDM, up to 120°F (245°C), Silicone, up to 240°F (460°C)

Maximum Operating Pressure/Maximum Vacuum Rating: up to 50% of the minimum stamped burst pressure
Burst Pressure Tolerance

- ± 15 mbarg for nominal burst pressures ≤ 100 mbarg; ± 0.25 psig for nominal burst pressure ≤ 1.5 psig
- ± 25 mbarg for nominal burst pressure ≤ 250 mbarg; ± 0.36 psig for burst pressure ≥ 1.5 and < 3.6 psig
- ± 50 mbarg for nominal burst pressure ≥ 250 mbarg; ± 0.75 psig for burst pressure ≥ 3.6 psig

Operating Temperature Range; -40 to 240°C / -40 to 460°F (continuous); up to 260°C / 500°F intermittent

Fike offers a wide range of standard Sani-V explosion vents in rectangular configurations with the following characteristics:

Explosion Vent Dimensions are Nominal				Burst Pressure (psi @ 72°F)		Bolts			External Dimensions	
Relief Area M ²	Relief Area Ft ²	Size mm	Size inches	Minimum	Maximum	Qty	D2	Size	mm	inches
.267	2.9	470 x 570	18.5 x 22	1.0	6.5	26	.5"	3/8"	578 x 678	22.75 x 26.7
.500	5.3	500 x 1000	19.5 x 39	.75	3.75	34	.5"	3/8"	608 x 1108	24 x 43.5
.509	5.4	566 x 900	22 x 35	.75	3.75	34	.5"	3/8"	674 x 1008	26.5 x 39.5
.809	8.7	900 x 900	35 x 35	.50	2.9	40	.5"	3/8"	1008 x 1008	39.5 x 39.5
.999	10.8	1000 x 1000	39 x 39	.50	2.9	44	.5"	3/8"	1108 x 1108	43.5 x 43.5

ACCESSORIES

The Sani-V can be supplied with electrical break-wire type burst indicator. For thermal/acoustic insulation an Ex-Cover is recommended.

All above data is subject to change without notice. They must not be used unless confirmed in writing



Copyright © Fike Corporation All Rights Reserved.
Form No. X.1.11.01-2 September, 2007 Specifications are subject to change without notice.